

Signal lamp 5 functions

SY-5F - Direct voltage - Ø 22mm

Faz/engineering
Innovative and industrial signage and applications

by **Fazim/Group**



Reference :

SY-5F + VOLTAGE + CC + COLORS + 22

Example : SY-5F24CCVRVJBe22

Generalities

The signal lamps **SY-5F**, in direct-voltage, allow the visualisation of 5 different functions on the same LED lamp. They have a fixed light and can be used to differentiate the different states of a working device. The robustness of these indicators can be installed in disturbed and humid environments.

Description

- Body : Co-polyamide , fixing plastic nut, diameter 22 mm (0.866"), IK10, IP67 in front face, through the flat gasket provided, RoHS compliant, CE, UL 94 V-0.
- Front face : 5 color LED : red (R), green (V), yellow (J), amber (I), white (Bc), orange (O) or blue (Be) high brightness + 1 transparent cap. (Other LED colors in option)

Technical specifications

- Supply voltages (+/-20%) and consumptions for 1 function :

Voltages Colors	12Vdc	24Vdc	48Vdc
R, J, I, O, Be	-	210 mW	-
V, Bc	-	100 mW	-

- Conformities : Norms EN55015, EN61547, EN61000-6-2, EN61000-6-4, ROHS, Reach, CE.
- Lifetime (MTBF*) : 100 000 hours.
- Operating temperature : -30°C à +70°C (22°F to 158°F).
- IP protection standard : IP67 (in front face).
- IK protection standard : IK10.

(* : mean time between failure)


Advantages

- Insensitivity to vibrations, mechanical shocks.
- Resistance to moisture and water splashes.
- Electrical shocks resist : 5KV during 50µs.
- Immunity against magnetic fields.
- Assembly and disassembly easy, fast and secure .
- Exceptionally long life and unparalleled.
- Low power consumption and heat dissipation.



Connections


- 1 Quick-Fit male terminal 6.3mm (0.248")
- 5 Quick-Fit male terminals 2.8mm (0.110")



C = Common (-) (Common cathodes)


- 1 = LED 1 ignition (+)
- 2 = LED 2 ignition (+)
- 3 = LED 3 ignition (+)
- 4 = LED 4 ignition (+)
- 5 = LED 5 ignition (+)

Electrical symbol



Mechanical specifications

- Fixing : standard drilling Ø 22mm +/-0.5mm ; (Ø 0.866").



Working

• Off :



• On :



Between C(-) and 1(+)




Between C(-) and 2(+)



Between C(-) and 3(+)



Between C(-) and 4(+)



Between C(-) and 5(+)



Between C(-) and 1(+) to 5(+)



Options an warranty

- Options : Other voltage on request, threshold voltage, color LED (Pink Ro and Purple Vi), color cap, output wiring terminals, snap contact with screw or a connector of your choice...
- Warranty : 24 months manufacturer. No Quick-Fit Terminal Male must be welded or lose the guarantee.
- Recommendation : The Quick-Fit Terminal Male must be completely covered with isolation that can be removed only by destruction.